

Lightweight Neoprene Hose NEO-1™ 3001 Series

I.D. INCHES	DASH NO.	P.S.I.G.	BURST	MAX. LEAKAGE CFM	MAX. NEG. P.S.I.	WT. PER FT. IN OZ.	CUFF LENGTH	WALL THICKNESS
1.00	4	35	70	.02	15	1.7	1 1/2	.040
1.25	5	35	70	.02	15	2.1	1 1/2	.040
1.50	6	25	30	.03	13	2.5	1 1/2	.040
1.75	7	20	50	.03	13	3.0	1 1/2	.040
2.00	8	15	40	.04	10	3.4	1 1/2	.045
2.25	9	15	40	.05	10	3.8	1 1/2	.045
2.50	10	10	35	.05	8	4.3	1 1/2	.045
2.75	11	10	30	.06	8	4.7	1 1/2	.045
3.00	12	10	30	.065	7	5.1	1 1/2	.050
3.25	13	10	30	.065	6	5.3	1 1/2	.050
3.50	14	10	25	.07	6	6.0	1 1/2	.050
3.75	15	9	25	.08	5	6.5	1 1/2	.050
4.00	16	9	25	.09	5	7.0	1 1/2	.055
4.50	18	8	20	.10	4	7.7	2	.055
5.00	20	7	20	.125	4	8.7	2	.055
5.50	22	6	15	.13	4	9.3	2	.055
6.00	24	5	15	.14	3	10.6	2	.060
8.00	32	4	12	.16	.3	12.4	2	.065
10.00	40	3	9	.18	2	17.8	2 1/2	.080
12.00	48	2	6	.20	2	20.4	2 1/2	.080

Temperature range -65°F to +300°F (-54°C to +149°C)
 NEO 1 AND 2 Military Specification: NAS 1370-1379 (2ply), MIL-H-8796 (2 ply), MIL-H-62028. NEO 3: MIL-H-52079.
 Compresses to 1/2 of extended length. Bend radius is one times diameter of hose.