

Lightweight Neoprene Hose NEO-2™ 1001 Series

I.D. INCHES	DASH NO.	P.S.I.G.	BURST	MAX. LEAKAGE CFM	MAX. NEG. P.S.I.	WT. PER FT. IN OZ.	CUFF LENGTH	WALL THICKNESS
1.00	4	60	180	.02	15	2.0	1 1/2	.060
1.25	5	60	180	.02	15	2.5	1 1/2	.060
1.50	6	55	165	.02	13	3.0	1 1/2	.060
1.75	7	55	165	.025	13	3.5	1 1/2	.060
2.00	8	50	150	.025	10	4.0	1 1/2	.060
2.25	9	50	150	.025	10	4.5	1 1/2	.060
2.50	10	50	150	.030	8	5.0	1 1/2	.060
2.75	11	45	135	.025	8	6.0	1 1/2	.070
3.00	12	45	135	.05	7	6.2	1 1/2	.070
3.25	13	45	135	.05	6	6.7	1 1/2	.070
3.50	14	40	120	.06	6	7.2	1 1/2	.070
3.75	15	40	120	.07	5	7.8	1 1/2	.070
4.00	16	40	120	.075	5	8.4	1 1/2	.070
4.50	18	35	105	.09	4	9.6	1 1/2	.070
5.00	20	35	105	.10	4	10.7	2	.080
5.50	22	30	90	.12	4	11.8	2	.080
6.00	24	30	90	.15	3	13.0	2	.080
8.00	32	15	45	.175	3	17.8	2	.090
10.00	40	8	24	.2	2	22.6	2 1/2	.100
12.00	48	4	18	.3	2	27.1	2 1/2	.100

Temperature range -65°F to +300°F (-54°C to +149°C)

NEO 1 and 2 Military Specification: NAS 1370-1379 (2 ply), MIL-H-8796 (2 ply), MIL-H-62028. NEO3: MIL-H-52079

Compresses to 1/2 of extended length. Bend radius is one times diameter of hose.