

AVIAQUIP

NAS679A LOW HEIGHT HEX



**CARBON STEEL - TYPE 2 CLASS 2 CAD
PLATED - 450 DEG. DRY FILM LUBE**


TO FIT DIA.	NAS 679A		
#440	A04		
#632	A06		
#832	A08		
#1032	A3		
1/4-28	A4		
5/16-24	A5		
3/8-24	A6		
7/16-20	A7		

MS17825 FULL HEIGHT MS17826 LOW HEIGHT SELF LOCKING CASTLE NUT



MS17825


ALLOY STEEL
CAD PLATED



MS17826

THREAD SIZE	MS17825	MS17826
#10-32	3	3
1/4-28	4	4
5/16-24	5	5
3/8-24	6	6
7/16-20	7	7
1/2-20	8	8


MS21025 SUPERSEDES AN7502 CASTELLATED HEX NUT



DASH NO.	SIZE	B	F
-15	.9375-16 UN-3B	1.250	1.448
-16	1.0000-16 UN-3B	1.250	1.448
-20	1.2500-16 UN-3B	1.50	1.732
-23	1.4375-16 UN-3B	1.688	1.948
-24	1.5000-16 UN-3B	1.750	2.021
-28	1.7500-16 UN-3B	2.125	2.454
-31	1.9375-16 UN-3B	2.250	2.596
.32	2.0000-16 UN3B	2.250	2.596
-38	2.4375-16 UNS-3B	2.875	3.319
-47	2.9375-16 UNS-3B	3.500	4.060
-56	3.4375-15 YNS-3B	4.000	4.619

NAS509

CORNER DRILLED JAM NUT
4130 STEEL - CAD PLATED
A286 CRES- PASSIVATED



-L = LEFT HANDED -R = RIGHT HANDED

DASH #	THREAD SIZE	WRENCH SIZE	HEIGHT	HOLE SIZE
06	6-32	5/16	.125	.035
08	8-32	11/32	.125	
3	10-32	3/8	.156	.046
4	1/4-28	7/16	.188	
5	5/16-24	1/2	.219	
6	3/8-24	9/16	.250	
7	7/16-20	5/8	.261	
8	1/2-20	3/4	.313	
9	9/16-18	7/8	.375	.070
10	5/8-18	15/16	.406	
12	3/4-16	1 1/16	.469	
14	7/8-14	1 1/4	.500	
17	1" -12	1 1/2		
18	1 1/8 -12	1 5/8	.531	

TORQUE SEAL PUTTY



Torque Seal

Inspection putty is available in red, green, white, blue, orange, purple, brown, yellow and grey

1/2 ounce tube

Product information and part numbers shown on these pages are not guaranteed correct by AVIAQUIP PTY. LTD and are subject to change without notice.